

S-NC19 / S-SC19 / WM-NC19 Cabinets Accessories

The Cabinets 19" from the floor FOCUS-S and NC-SC and the cabinets 19" FOCUS WM-NC wall mounting, have a wide range of accessories that make the product customizable.

= WALL MOUNTED
 = STANDING



PLINTHS

They allow more stability up to 1.000 Kg
Color Grey RAL 7035
Black RAL 9004



EARTHING KIT

- Earthing Kit: length 300 mm
- Earthing Kit with screws



FIXED SHELVES 1U

Static load capacity: 90 Kg
Depth: 300 - 450 mm



FIXED SHELVES 1U

Static load capacity: 90 Kg
Depth: 350 - 550 - 720 mm



SLIDING SHELVES 1U

Static load capacity: 30 Kg



CANTILEVER SHELVES 2U

Static load capacity: 22 Kg



SLIDING SHELVES 1U

Max sliding: 260 mm



FAN UNITS

Fan unit with 2 fans
Width: 260 mm - Depth: 190 mm
Cable: H05VV-F 3G 0.75mm² x 1,5 m
Plug: 2 P + ⊕ Germany+France 16A 250V.
Presa C13
Color Grey RAL 7035
Black RAL 9004



FAN UNITS

Fan unit with 4 fans
Width: 375 mm - Depth: 260 mm
Cable: H05VV-F 3G 0.75mm² x 1,5 m
Plug: 2 P + ⊕ Germany+France 16A 250V.
Presa C13
Color Grey RAL 7035
Black RAL 9004



FAN UNITS

Dimensions: 120 x 120 x 38 mm
Housing: PBT
Blades: PBT
Operating temperature: -10°C ÷ +60°C
Humidity: 85% max
Voltage: 230V AC 50Hz (110V-60Hz on demand)
Life 50.000 hours with ball bearing



POWER DISTRIBUTION UNITS 1U

Sockets: Germany + Italy 10/16A 250V x 7
Plug: Germany 16A 250V
Size: 19" 1U
Cable: H05VV - F 3G 1,5mm² x 3 m
Load: 3,5 KW max.
Protection: Mini circuit breaker 2P, 16A 250V with cover



POWER DISTRIBUTION UNITS 1U

Sockets: Germany + Italy 10/16A 250V x 8
Plug: Germany 16A 250V
Size: 19" 1U
Cable: H05VV - F 3G 1,5mm² x 3 m
Load: 3,5 KW max.
Protection: Switch ON/OFF with lamp



CASTORS AND ADJUSTABLE FEET

- Castors for cabinets Dia 50 mm Without break
- Castors for cabinets Dia 50 mm With break
- Set with 2 castors without break, + 2 with break
- M12 Adjustable feet set - 4 pcs